Material Safety Data Sheet



1. Identification of the material and supplier

Product name Transmission Oil JSD OX-46 (DX2)

SDS no. 460828

Product use Transmission fluid

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Supplier BP Australia Pty Ltd (ABN 53 004 085 616)

717 Bourke Street Docklands VIC 3008

Australia

Tel: +61 (03) 9268 4111 Fax: +61 (03) 9268 3321

EMERGENCY TELEPHONE

NUMBER

+61 29032 0460 (or 1800 14 14 74 within Australia)

Product code 460828-AU07

2. Hazards identification

Statement of hazardous/dangerous nature

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

3. Composition/information on ingredients

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

This product does not contain any hazardous ingredients at or above regulated thresholds.

4. First-aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention if irritation occurs.

Skin contact Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation

develops

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms appear.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth

to an unconscious person. If potentially dangerous quantities of this material have been swallowed,

call a physician immediately.

Advice to doctor Treatment should in general be symptomatic and directed to relieving any effects.

5. Fire-fighting measures

Extinguishing media

Suitable In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.

Not suitable Do not use water jet.

Hazardous decomposition Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide

Unusual fire/explosion

hazards

This material is not explosive as defined by established regulatory criteria.

Special fire-fighting None identified. procedures

Protection of fire-fighters Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout

gear.

Product name Transmission Oil JSD OX-46 (DX2)

Product code 460828-AU07

Page: 1/4

Version 2.01

Date of issue 11 November 2010

Format Australia

(Australia)

(ENGLISH)

Accidental release measures

Personal precautions No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding

areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through

spilt material. Put on appropriate personal protective equipment (see section 8).

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform

the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or

air).

Large spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses,

basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact

information and section 13 for waste disposal.

Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-

soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage Keep container tightly closed. Keep container in a cool, well-ventilated area.

Combustibility Classification Combustible liquid Class C2 (AS 1940).

8. Exposure controls/personal protection

Ingredient name
Occupational exposure limits
Base oil - unspecified
Safe Work Australia (Australia).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Whilst specific OELs for certain components are included in this SDS, it should be noted that other components of the preparation will be present in any mist, vapour or dust produced. For this reason, the specific OELs may not be applicable to the product and are provided for guidance purposes.

Biological Limit Values No biological limit allocated.

Exposure controls

Occupational exposure Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of

controls vapours below their respective occupational exposure limits.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking

and using the lavatory and at the end of the working period.

Personal protective equipment

Respiratory protection Avoid breathing of vapours, mists or spray. Select and use respirators in accordance with AS/NZS

1715/1716. When mists or vapours exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapour and dust/mist (Type P1) filters. Filter

capacity and respirator type depends on exposure level.

Skin and body Avoid prolonged or repeated contact with skin. Wear protective clothing if prolonged or repeated

contact is likely.

Hand protection Wear protective gloves if prolonged or repeated contact is likely. Chemical-resistant gloves.

Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer

and with a full assessment of the working conditions.

Eye protection Safety glasses with side shields.

9. Physical and chemical properties

Physical stateLiquid.ColourRed. ClearOdourMild

Flash point 180 °C (Closed cup) Pensky-Martens.

Vapour pressure Not available.
Vapour density Not available.

Viscosity Kinematic: 34 mm²/s (34 cSt) at 40°C

Kinematic: 6.9 to 7.5 mm²/s (6.9 to 7.5 cSt) at 100°C

pH Not available.Boiling point / range Not available.

Product name Transmission Oil JSD OX-46 (DX2)

Product code 460828-AU07 Page: 2/4

Version 2.01 Date of issue 11 November 2010 Format Australia Language ENGLISH

(Australia) (ENGLISH)

Melting point / range Not available.

Pour point -40 °C

Relative density/Specific

gravity

Not available.

Density 868 kg/m³ (0.868 g/cm³) at 15°C

Solubility insoluble in water.

10 . Stability and reactivity

Stability The product is stable.

Conditions to avoid Avoid extreme temperatures, strong oxidizers, fire.

Incompatibility with various

substances/Hazardous

Reactions

products

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition Decomposition products may include the following materials:

carbon dioxide carbon monoxide

11. Toxicological information

Effects and symptoms

Eyes No significant health hazards identified.

Skin Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

InhalationNo significant health hazards identified.IngestionNo significant health hazards identified.

Chronic toxicity

Carcinogenic effects

No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen by

ACGIH, the International Agency for Research on Cancer (IARC), the European Commission (EC), or

the National Occupational Health and Safety Commission (Australia).

Mutagenic effects No known significant effects or critical hazards.

12 . Ecological information

Ecotoxicity Not classified as environmentally hazardous in accordance with the 'Approved Criteria for Classifying

Hazardous Substances' [NOHSC (1008)/2004 as amended and adapted].

Biodegradability

Persistence/degradability The biodegradability of this material has not been determined.

13. Disposal considerations

Disposal considerations / Waste information

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration No additional special precautions identified.

14. Transport information

International transport regulations

Not classified as dangerous for transport (ADG, IMDG, ICAO/IATA).

Special precautions for user No known special precautions required. See Section: "Handling and storage" for additional

information.

15 . Regulatory information

Standard for the Uniform Scheduling of Drugs and Poisons

Not regulated.

Control of Scheduled Carcinogenic Substances

Ingredient name Schedule

Australia Regulations

No Listed Substance

Labelling requirements for SUSDP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with NOSHC National Code of Practice for labelling of workplace substances.

Product name Transmission Oil JSD OX-46 (DX2) Product code 460828-AU07 Page: 3/4

Version 2.01 Date of issue 11 November 2010 Format Australia Language ENGLISH

(Australia) (ENGLISH)

Other regulations All components are listed or exempted. Europe inventory **United States inventory** All components are listed or exempted.

(TSCA 8b)

Australia inventory (AICS)

All components are listed or exempted.

Canada inventory All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (ENCS) At least one component is not listed. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** All components are listed or exempted.

(PICCS)

16. Other information

Key to abbreviations

AMP = Acceptable Maximum Peak

ACGIH = American Conference of Governmental Industrial Hygienists, an agency that promulgates exposure standards.

ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail ADG Code = Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number = Chemical Abstracts Service Registry Number HAZCHEM Code = Emergency action code of numbers and letters which gives information to

emergency services. Its use is required by the ADG Code for Dangerous Goods in bulk. ICAO = International Civil Aviation Organization.

IATA = International Air Transport Association, the organization promulgating rules governing shipment of goods by air.

IMDG = International Maritime Organization Rules, rules governing shipment of goods by water. IP 346 = A chemical screening assay for dermal toxicity. The European Commission has recommended that Method IP 346 be used as the basis for labelling certain lubricant oil base stocks

for carcinogenicity. The EU Commission has stipulated that the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. (See Note L, European Commission Directive 67/548/EEC as amended and adapted.) DMSO is a solvent.

NOHSC = National Occupational Health & Safety Commission, Australia

TWA = Time weighted average STEL = Short term exposure limit

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

History

Date of issue 11/11/2010. Date of previous issue 19/01/2010. **Product Stewardship**

Prepared by Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name Transmission Oil JSD OX-46 (DX2)

Version 2.01 Date of issue 11 November 2010 Product code 460828-AU07

Language ENGLISH (ENGLISH)

Page: 4/4

(Australia)

Format Australia