

Mobil Delvac MX 15W-40

Premium Commercial Engine Oil

The Mobil logo consists of the word "Mobil" in a blue, sans-serif font. A red arc is positioned above the letters "i" and "l", starting from the top right and curving towards the left.

Product Description

Mobil Delvac MX 15W-40 is a premium commercial multipurpose engine oil formulated from high quality mineral base oils and a superior balanced additive system to meet the severe service demands of modern diesel and gasoline engines. It provides outstanding protection against oil thickening, high temperature engine deposits, sludge build up, oil degradation and corrosion. It has excellent low temperature properties, which ensure ready oil circulation on start-up to prevent wear, while its "stay in grade" shear stability enables it to maintain viscosity under severe, high temperature operations.

Specifications

Recommended for use in applications requiring API CI-4/CH-4 / CG-4 / CF-4/CF/SJ/SL; ACEA A2-96 Issue 3/B3-98 Issue 2/B4-02/E3-96 Issue 4/E5-02; MB 228.3/229.1; MAN M3275, Mack EO-M-PLUS/EO-M, Volvo VDS2 and VDS3; RVI RLD; CES 20078/20077/20076/20072/20071; Allison C-4.

Benefits/Advantages

- Enhanced protection for four-cycle diesel engines in the most demanding on and off-highway service.
- Prolonged engine life.
- Outstanding control of high temperature deposits.
- Excellent soot control.
- Reduced engine scuffing and bore-polishing due to enhanced high temperature/high shear viscosity retention.
- Improved low temperature sludge control in stop-and-go service.
- Easy starting in cold weather conditions.
- Extended TBN quality reserve for long term wear and deposit control.
- Reduced oil consumption due to improved high temperature performance.

Application

Mobil Delvac MX 15W-40 is recommended for use in the most severe service applications of modern on-and off-highway diesel engines. It extends engine life between overhauls in high speed/ high load operations and in pick-up/delivery operation modes in four-cycle diesel engines. It is also recommended for use in high performance gasoline engines, offering one oil for mixed fleet operations.



Typical Properties

Mobil Delvac MX	15W-40
SAE Grade	15W-40
Viscosity cSt at 40°C	104
cSt at 100°C	14.2
CCS Viscosity cP at -20°C	6630
Viscosity Index, min	125
Sulphated Ash, wt%, max	1.25
Total Base Number (TBN) mg KOH/g, max	11
Flash Point, °C, min	215
Pour Point, °C, max	-27

Health and Safety

Based on available toxicological information, this product produces no adverse effects on health when properly handled and used. No special precautions are suggested beyond attention to good personal hygiene, including laundering oil-soaked clothing and washing skin contact areas with soap and water. Additional health and safety information on this product, including Material Safety Data Bulletins, is available on request from your local ExxonMobil company.

ExxonMobil Middle East Marketing Corporation
P. O. Box 33369, Dubai, U.A.E.

Mobil Delvac MX 15W-40
November 2003 All rights reserved

Due to continual product research and development, the information contained herein is subject to change without notice.