# Mobilgrease FM 102

# **Food Machinery Grease**



## **Product Description**

Mobilgrease FM 102 is pale yellow colored, premium food machinery grease. It is an NLGI Grade 2 and is formulated with an aluminum complex thickener. It is unique in the way it combines suitability in food applications with superior performance in the lubrication of machinery and bearings.

#### Benefits/ Advantages

- · Extended lubricant life at high temperatures.
- Excellent water tolerance.
- Increased protection against corrosion.
- · Good low temperature pumpability.

#### Application

Mobilgrease FM 102 is formulated to lubricate journal and anti-friction bearings on both inplant food machinery and mobile equipment handling food products. It will withstand the elevated temperatures and wet environment common in most food plants. It meets FDA regulation 178.3570 and has USDA type H-1 and FDA approvals for lubricants with incidental food contact.



## **Typical Properties**

Mobilgrease FM

102

**NLGI** Grade

2

Thickener Type

Aluminum Complex

Texture

Smooth

Color

Pale Yellow

Dropping Point, °C

216

Base Oil Viscosity

cSt at 40°C

108

cSt at 100°C

12

Penetration, Worked

285

### Health and Safety

Based on available toxicological information, this product produces no adverse effects on health when properly handled and used. No special precautions are suggested beyond attention to good personal hygiene, including laundering oil-soaked clothing and washing skin contact areas with soap and water. Additional health and safety information on this product, including Material Safety Data Bulletins, is available on request from your local ExxonMobil company.

Exxo	nMobil	Middle	East	Marketing	Corporation
000	00000	The state of the			

Mobilgrease FM 102

P.O. Box 33369, Dubai, U.A.E.

November 2003 All rights reserved

Due to continual product research and development, the information contained herein is subject to change without notice.