



1 . Identification of the material and supplier

Product name	Energol IC-HFX 403
SDS #	401794
Product use	Engine oils. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	BP Australia Pty Ltd (ABN 53 004 085 616) Melbourne Central, 360 Elizabeth Street, Melbourne, Victoria 3000, Australia Tel: +61 (03) 9268 4111 Fax: +61 (03) 9268 3321
EMERGENCY TELEPHONE NUMBER	1800 14 14 74
OTHER PRODUCT INFORMATION	Technical Help Line 1 300 139 700 (Local Call)
Product code	401794-AU11, -AU31, -AU53

2 . Hazards identification

Statement of hazardous/dangerous nature	NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.
--	---

3 . Composition/information on ingredients

Highly refined mineral oil and additives

This product does not contain any hazardous ingredients at or above regulated thresholds.

4 . First-aid measures

Eye contact	In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

5 . Fire-fighting measures

Extinguishing Media	
Suitable	In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.
Not Suitable	Do not use water jet.
Hazards from combustion products	These products are carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide).
Unusual fire/explosion Hazards	This material is not explosive as defined by established regulatory criteria.
Special fire-fighting procedures	None identified.
Protection of fire-fighters	Fire-fighters should wear self-contained positive pressure breathing apparatus (SCBA) and full turnout gear.

Product name Energol IC-HFX 403	Product code 401794-AU11, -AU31, -AU53	Page: 1/5
Version 1	Date of issue 13 June 2006	Format Australia (Australia)
		Language ENGLISH
Build 2.4.0		

6 . Accidental release measures

Emergency Procedures	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
Methods and materials for containment and clean-up	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilt material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
Personal protection in case of a large spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

7 . Handling and storage

Handling	Wash thoroughly after handling. Avoid strong oxidisers.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area.
Combustibility Classification	Combustible liquid Class C2 (AS 1940).

8 . Exposure controls/personal protection

Ingredient name	Occupational exposure limits
Base oil - unspecified	NOHSC (Australia). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral
Whilst specific OELs for certain components are included in this SDS, it should be noted that other components of the preparation will be present in any mist, vapour or dust produced. For this reason, the specific OELs may not be applicable to the product and are provided for guidance purposes.	
Biological Limit Values	No biological limit allocated.
Control Measures	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Personal protective equipment	
Respiratory system	Avoid breathing of vapors, mists or spray. Select and use respirators in accordance with AS/NZS 1715/1716. When mists or vapors exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapor and dust/mist (Type P1) filters. Filter capacity and respirator type depends on exposure level.
Skin and body	
Hands	Wear protective clothing if prolonged or repeated contact is likely. Wear protective gloves if prolonged or repeated contact is likely. Chemical resistant gloves. Recommended: nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Eyes	Safety glasses with side shields.

9 . Physical and chemical properties

Physical state	Liquid.
Colour	Amber.
Odour	Oily.
Flash point	>200 °C (Closed cup) Pensky-Martens.
Pour Point	-6 °C
Viscosity Index	102
Boiling point / range	Not available.
Melting point / range	Not available.
Density	910 kg/m ³ (0.91 g/cm ³) at 15°C
Vapour density	Not available.
Vapour pressure	Not available.

Product name Energol IC-HFX 403

Product code 401794-AU11,
-AU31, -AU53

Page: 2/5

Version 1

Date of issue 13 June 2006

Format Australia
(Australia)

Language ENGLISH

Build 2.4.0

Solubility	Insoluble in water.
pH	Not available.
Relative density	Not available.
Viscosity	Kinematic: 94 mm ² /s (94 cSt) at 40°C Kinematic: 11.5 mm ² /s (11.5 cSt) at 100°C

10 . Stability and reactivity

Stability	The product is stable.
Conditions to Avoid	Avoid extreme temperatures, strong oxidizers, fire.
Incompatibility with various substances/Hazardous Reactions	Reactive with oxidising agents.
Hazardous Decomposition Products	These products are carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide).

11 . Toxicological information

Effects and symptoms

Eyes	Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Skin	Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.
	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Inhalation	At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility.
Ingestion	Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.

Chronic toxicity

Carcinogenic effects	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen by ACGIH, the International Agency for Research on Cancer (IARC), the European Commission (EC), or the National Occupational Health and Safety Commission (Australia).
-----------------------------	---

12 . Ecological information

Ecotoxicity	Not classified as environmentally hazardous in accordance with the 'Approved Criteria for Classifying Hazardous Substances' [NOHSC (1008)/2004 as amended and adapted].
Persistence/degradability	The biodegradability of this material has not been determined.
Mobility	Spillages may penetrate the soil causing ground water contamination.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13 . Disposal considerations

Disposal Consideration / Waste information	Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.
Special Precautions for Landfill or Incineration	No additional special precautions identified.

14 . Transport information

Not classified as dangerous for transport (ADG, IMDG, ICAO/IATA).

Special precautions for user	No known special precautions required. See Section: "Handling and storage" for additional information.
-------------------------------------	--

Product name Energol IC-HFX 403	Product code 401794-AU11, -AU31, -AU53	Page: 3/5
Version 1	Date of issue 13 June 2006	Format Australia (Australia)
	Language ENGLISH	
	Build 2.4.0	

15 . Regulatory information

Standard for the Uniform Scheduling of Drugs and Poisons

Ingredient name

No Listed Substance

Schedule

Control of Scheduled Carcinogenic Substances

Ingredient name

No Listed Substance

Schedule

Other Classification Information

Other regulations

Inventories

AUSTRALIAN INVENTORY (AICS): In compliance.

CANADA INVENTORY (DSL): In compliance.

CHINA INVENTORY (IECS): In compliance.

EC INVENTORY (EINECS/ELINCS): In compliance.

JAPAN INVENTORY (ENCS): In compliance.

KOREA INVENTORY (ECL): In compliance.

PHILIPPINE INVENTORY (PICCS): In compliance.

US INVENTORY (TSCA): In compliance.

16 . Other information

Key to abbreviations

AMP = Acceptable Maximum Peak

ACGIH = American Conference of Governmental Industrial Hygienists, an agency that promulgates exposure standards.

ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail

ADG Code = Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number = Chemical Abstracts Service Registry Number

HAZCHEM Code = Emergency action code of numbers and letters which gives information to emergency services. Its use is required by the ADG Code for Dangerous Goods in bulk.

ICAO = International Civil Aviation Organization.

IATA = International Air Transport Association, the organization promulgating rules governing shipment of goods by air.

IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.

IP 346 = A chemical screening assay for dermal toxicity. The European Commission has recommended that Method IP 346 be used as the basis for labelling certain lubricant oil base stocks for carcinogenicity. The EU Commission has stipulated that the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. (See Note L, European Commission Directive 67/548/EEC as amended and adapted.) DMSO is a solvent.

NOHSC = National Occupational Health & Safety Commission, Australia

TWA = Time weighted average

STEL = Short term exposure limit

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

History

Date of issue

13/06/2006.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third

Product name Energol IC-HFX 403

Product code 401794-AU11,
-AU31, -AU53

Page: 4/5

Version 1

Date of issue 13 June 2006

Format Australia
(Australia)

Language ENGLISH

Build 2.4.0

party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name Energol IC-HFX 403

Product code 401794-AU11,
-AU31, -AU53

Page: 5/5

Version 1

Date of issue 13 June 2006

Format Australia
(Australia)

Language ENGLISH

Build 2.4.0