

CORROSION PREVENTIVE OIL COMPOUND

C-629 – AIR 1502 (obsolete)

Description

Nycoprotec 02 is a solution of lanoline and resin in a mixture of white spirit and xylene.

Application

Nycoprotec 02 is intended to provide a temporary protection against corrosion of metallic parts made in steel and light alloys during storage, both for packaged and unpackaged parts.

Nycoprotec 02 leaves a red-coloured semi-hard film on the parts upon drying. Application is by dipping, brushing or spraying. The protective film may be removed by using white spirit.



Characteristic	Unit	Result	Limit*	Test method
- Appearance	-	red clear liquid	limpid	visual examination
- Specific gravity at 20°C	kg/dm ³	0.880	report	ASTM D 4052
- Flash point	°C	29	-	ASTM D 93
- Film thickness	µm	30 to 50	-	AIR 1655
- Covering capacity at 20°C	m ² /kg	10-12	-	-
- Rust protection: 48 h in seawater and 120 h distilled water	-	no corrosion	no corrosion	AIR 1502
- Dry extract mass fraction	%	50	-	NF-T-30011

* AIR 1502 specification

The values above are typical values. They do not constitute any contractual commitment. Sales specifications are available on request. The present technical data sheet replaces all the previous editions.