

## CORROSION PREVENTIVE OIL CONCENTRATE

C-608 – AIR 1503/B (obsolete) – MIL-C-6529 C Amd.2 Type 1

### Description

Nycoprotec 03 is a concentrate of anti-corrosion additives with a viscosity of 258 cSt at 40°C.

### Application

Nycoprotec 03 is intended to be diluted in petroleum piston engine oil or petroleum turbine engine oil. The typical rate is 3 parts of engine oil and 1 part of Nycoprotec 03 by volume.

It may also be used at a different treat-rate in various petroleum oils to impart to them good anti-corrosion properties.



Characteristic	Unit	Result	Test method
- Appearance	-	hazy	visual examination
- Specific gravity at 20°C	kg/dm <sup>3</sup>	0.902	ASTM D 4052
- Kinematic viscosity at 100°C 40°C	mm <sup>2</sup> /s	21.6 258	ASTM D 445
- Viscosity index	-	100	ASTM D 2270
- Flash point	°C	252	ASTM D 92
- Copper corrosion 3 h at 100°C	-	1a	ASTM D 130
- Conradson residue	%	0.4	ASTM D 189
- Oxidised Ash content	%	0.0	ASTM D 482

The values above are typical values. They do not constitute any contractual commitment.  
Sales specifications are available on request. The present technical data sheet replaces all the previous editions.